

## Description

Vintro Primer is water based, non-drip, low VOC, multipurpose primer/undercoat. Ideal for use over new or bare softwood surfaces, to seal the surface prior to painting.

## Sizes

Available in 1 Litre tins.

## Coverage

A 1 litre tin will cover approx 18m<sup>2</sup> - depending on the properties of the surface.

## Colour

Available in White and Grey.

## Thinner

In most cases the product does not require thinning prior to use.

## Drying times

Depending on room temperature and relative humidity, the product will normally be touch dry after 30 - 60 minutes. The surface can be recoated after 2 hours.

## Uses

For priming walls, wood and metal, interior or exterior.

## Technical properties

The product is easy to apply, including overhead, as it is virtually non-drip. It has excellent adhesion properties, dries quickly and is exceptionally low VOC.

## Biological properties

Vintro Primer is a non-toxic, non-hazardous, eco-friendly product made from locally sourced materials in an ecologically responsible way. Thanks to its composition it is virtually innocuous for people and environment. Vintro paints fall into the industry's lowest possible eco-rating, so you don't need to worry about respiratory issues or smell as the products are virtually odourless.

## Application

### Temperature

Apply the product in temperatures above 8 °C. The drying times mentioned, to a certain degree, depend on the room temperature and relative humidity.

### Preparation

The surface should be dry, and free from grease and dust.

### Application

Stir well before use. Apply using a good quality brush or roller.

### Tools

Brush, roller or a suitable spraying device. Use soapy water for cleaning the tools.

### Storage

Store containers tightly sealed in a cool but frost-free place. Shelf life: 24 months in original sealed container.

### Health & Safety

Keep coating materials, even if non-poisonous, out of the reach of children.

Always read the information on the tin before use. Ensure maximum ventilation during application and drying. Consult product material safety data sheet for further details.

### VOC Directive

EU limit value for this product: (cat A/a): 30g/l (2010) This product contains max. 30g/l VOC tinted.

### Local Manufacturing

All our paints are manufactured in our facility in the UK. We actively source suppliers who produce in an ecologically sustainable and environmentally responsible manner. We source raw materials from local suppliers wherever possible. We are committed to sustainable manufacturing, minimising pollution and minimising our energy and water consumption.

**Disclaimer** - Information contained on this Information Sheet is for guidance only. Advice is given in good faith and to the best of our knowledge but as application process, substrate quality and site conditions are outside of our control, figures stated may vary and no liability can be accepted on the basis of the information supplied. Always read relevant Information Sheets and SDS Sheets prior to use and test in a small area first or contact Vintro prior to use.